

HORN STROBE

AW-CSS2166-3

Purpose: The strobe horn fire alarm is a kind of terminal device for alarm; it is used for the sound & light alarm when the fire happens.

Feature: Adopt the two-wire or the four-wire system wiring method and the main line end receives two main lines, no polarization; and connect the power end to DC24V power line.



Technical specifications:

NO	Item	Parameters	Remarks
1	Temperature Range	-10~+50°C	
2	Humidity Range	≤95% RH	
3	Operating Voltage	DC12-DC24	
4	Working Current	≤300 mA	
5	Flash Period	≤1.0 S	
6	Alarm Sound	≥68 dB	
7	Flash Light Lifespan	≥40000 TIME	
8	Service life	10 years	

Installation:

1. At first , remove the cover of the horn strobe. Then punch two ϕ 3mm holes in the installation place (on the wall), the distance of the holes is 60mm, then put two plastic expansion plug into the two holes (if the wall is wooden material , it can be directly fixed with the self-tapping screws);
2. Connect to DC24V power, the red wire is positive polarity of power, black wire is the negative polarity of the power;
3. Use two self-tapping screws to fix the alarm in the installation place, and then tighten the screws.
4. Button on the cover.

Manufacturer:

ZHONGSHAN GUTA FIRE EQUIPMENT TECHNOLOGY CO.,LTD

Note:

This apparatus should be installed by the guidance of a competent person.

After hearing the fire alarm, you should call for help and timely evacuation from the fire prevention channel. If you can please timely alarm.